


# Aerial Work Platforms

## IWP<sup>®</sup> Super Series<sup>™</sup>

### Specifications



Models	IWP-20S		IWP-25S		IWP-30S	
Measurements	US	Metric	US	Metric	US	Metric
Working height*	26 ft 3 in	8.17 m	30 ft 11 in	9.6 m	35 ft 6 in	11 m
Platform height	20 ft 3 in	6.17 m	24 ft 11 in	7.6 m	29 ft 6 in	9 m
<b>A</b> Horizontal outreach**	2 ft 2 in	0.61 m	—	—	—	—
<b>B</b> Height - stowed:						
fully lowered	6 ft 4 in	1.93 m	6 ft 4 in	1.93 m	6 ft 4 in	1.93 m
base raised	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m
<b>C</b> Length	5 ft	1.52 m	5 ft	1.52 m	5 ft	1.52 m
<b>D</b> Width - standard base	2 ft 8 in	0.81 m	2 ft 8 in	0.81 m	—	—
wide base	—	—	—	—	3 ft 4 in	1.02 m
Corner access***	6 in	0.15 m	6 in	0.15 m	7 in	0.18 m

### Productivity

Lift capacity:	350 lbs	159 kg	350 lbs	159 kg	350 lbs	159 kg
with outreach option	300 lbs	136 kg	—	—	—	—
Platform Dimensions (l/w/h)						
Standard	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm
Gated standard	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm
Gated narrow	26/20/44.75 in	66/51/114 cm	26/20/44.75 in	66/51/114 cm	26/20/44.75 in	66/51/114 cm
Standard fiberglass**	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm

### Power

AC models	110 V / 50-60 Hz or 220 V / 50-60 Hz
DC models	12V

### Weight\*\*\*\*

#### Standard base

ANSI/CSA (AC)	1,245 lbs	564 kg	1,290 lbs	585 kg	—	—
ANSI/CSA (DC)	1,345 lbs	610 kg	1,390 lbs	630 kg	—	—

#### Standard base with outreach option

ANSI (AC)	1,350 lbs	612 kg	—	—	—	—
ANSI (DC)	1,450 lbs	658 kg	—	—	—	—

#### Wide base

ANSI (AC)	—	—	—	—	1,430 lbs	649 kg
ANSI (DC)	—	—	—	—	1,530 lbs	694 kg

### Standards Compliance

ANSI A92.3, CSA B354.1, EN 280, AS 1418.10

\* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

\*\* Horizontal outreach option available only on the IWP-20S, not available with fiberglass platform

\*\*\* Corner of platform top rail to corner of wall with ability to rotate leveling jack handle.

\*\*\*\* Weight will vary depending on options and/or country standards.

### Features

#### Standard Features

##### Measurements

###### IWP-20S

- 26 ft 2 in (8.15 m) working height
- 20 ft 2 in (6.15 m) platform height
- 2 ft 8 in (0.81 m) standard base width
- Outreach option adds 2 ft 2 in (0.66 m) of horizontal reach
- Up to 350 lbs (159 kg) lift capacity

###### IWP-25S

- 30 ft 5 in (9.44 m) working height
- 24 ft 5 in (7.44 m) platform height
- 2 ft 8 in (.81 m) standard base width
- Up to 350 lbs (159 kg) lift capacity

###### IWP-30S

- 35 ft 6 in (11 m) working height
- 29 ft 6 in (9 m) platform height
- 3 ft 4 in (1.02 m) wide base width
- Up to 350 lbs (159 kg) lift capacity

##### Productivity

- Standard base (IWP<sup>™</sup>-20S and 25S only)
- Sliding mid-rail standard platform
- Auxiliary platform lowering
- Most rigid mast in the industry
- Standard base rolls through standard doorways
- Wide base rolls through double doorways
- AC power to platform
- Dual activated up/down switch
- Ground fault interrupter lower receptacle
- Tie down attachment points
- Overhead crane attachment point
- Wide forklift pockets
- Built-in level sensing with interlocks

##### Power

- DC power with worldwide automatic smart charging system (12V / 110V / 230V / 50-60 Hz)

#### Options & Accessories

##### Productivity

- Outreach option (IWP-20S only) (not available for CSA)
- Operational warning light and descent alarm package
- Tool tray
- Fluorescent tube caddy
- Platform locating laser light

##### Power

- Power wheel assist with dual battery package\*
- Dual battery package (DC only)
- AC power 85V, 110V or 220V / 50-60 Hz

##### Platform

- Gated standard platform
- Gated narrow platform
- Standard fiberglass platform\*\*

##### Base

- Wide base (IWP<sup>™</sup>-30 only)



Shown with optional power wheel assist

\* Adds 12.5 in (.32 m) to unit length and 285 lbs (129 kg) to unit weight, DC only  
\*\* Not available with Outreach package

#### Genie United States

6464 185th Ave. NE  
Redmond, WA 98052  
Telephone +1 (425) 881-1800  
Toll Free in USA/Canada +1 (800)-536-1800  
Fax +1 (425) 883-3475

#### Distributed By: