

# Pioneer Industrial Doors



# SealTight Doors

## 400ST Fabric Door

850ST Available For Extra Large Door Size



\* Wind Load Varies by Door Size

\*\* Larger Sizes Available up to 30'W x 30'H

- ❖ Wind Loads of up to 80 mph \*
- ❖ Standard Sizes Up to 24'W x 20' H\*\*
- ❖ Manaras Operator or Manual Chain Hoist
- ❖ Opening Speeds 8" to 10" Per second
- ❖ Floating Bottom Bars for Safety
- ❖ Unique 100% Sealing System
- ❖ Easy to Clean Aluminum Tracks and Cover

## Freezer Door

- ❖ Digitally Controlled Condensation Management System (CMS)
- ❖ Smart 50 Microprocessor Controller, Digital Encoder
- ❖ R-4 Insulation Value
- ❖ Opening Speeds up to 48"/Second
- ❖ Easy to Clean Aluminum Tracks and Cover
- ❖ Curtain and Tracks Magnetically Sealed





\* Wind Load Varies by Door Size

\*\*Opening Speeds Vaies by Door Size

## 500ST/600ST High Speed Doors

- ❖ Wind Loads of up to 80 mph\*
- ❖ Standard Sizes Up to 20'W x 22'H
- ❖ Opening Speeds up to 50"/Second \*\*
- ❖ Fully Programmable Smart Controller
- ❖ Floating Bottom Bars, Leading Edge Sensor & Photo Eyes for Safety
- ❖ Unique 100% Sealing System
- ❖ Easy to Clean Aluminum Tracks and Cover
- ❖ Energy Efficient Motor Converts Single-Phase Power to 3-Phase

## RollRight II Door

- ❖ Opening Speeds up to 36" Per Second
- ❖ Wind Loads up to 45 mph \*
- ❖ Standard Sizes Up to 16'W x 16'H
- ❖ Exchangable Panels Available for Multi-Seasonal Use
- ❖ Fiberglass Windbars Won't Bend or Break
- ❖ Automatically Resets After Impact
- ❖ Low Maintenance - No Cables, Wheels, Springs, or Sewn Construction



\* Wind Load Varies by Door Size



# Specialty Doors



## NoPest Doors

- ❖ 11 oz. Vinyl Coated Mesh Polyester Screen
- ❖ Available in Spring Assisted, Chain Hoist, Sliding or Motorized. Up to 36" Per Second Opening Speed
- ❖ Standard Sizes Up to 14'W x 14'H
- ❖ Horizontal Stiffeners Bend if Loaded - Will Not Break or Kink
- ❖ Double Baffle Valance (at Top), EPDM Seals on Both Sides, Prevent Pest Intrusion
- ❖ Helps Meet FDA Requirements

## Clear-Flex Strip Door

- ❖ Reduces Heat Loss by up to 90%
- ❖ Available in Ribbed, Low Temp, Weld, and Dayglow Strips
- ❖ Prevents Movement of Dust and Other Contaminants from One Area to Another



## Air Curtain



- ❖ Provides a Thermal Barrier that Separates One Environment From Another
- ❖ Promotes Safety, By Providing an Unobstructed View of Doorways
- ❖ Widths Ranging from 2.5' to 30' and Heights Up to 30'

## Security Gate



- ❖ Provides Ability to Control Access
- ❖ Custom Built Solutions Suit Any Opening
- ❖ Provides Around the Clock Security (Locking Bars Included)
- ❖ Center Lock (Split Gate) Standard, (Single Open Gate Available)

